# 磐亞股份有限公司



## PAN ASIA CHEMICAL CORPORATION

100台北市中正區新生南路一段50號11樓

11F, No. 50, Sec. 1, Hsin Sheng South Rd., Taipei, 100 Taiwan

Tel:+886-2-2351-1212 Fax:+886-2-2396-2946 http://www.pacc.com.tw E-mail:paccsale@pacc.com.tw

### **SPECIFICATION**

產品名稱 (brand name)	PANESTER PEG 600 DOC
INCI name	聚乙二醇雙油酸酯 Polyethylene glycol dioleate
中文名稱 (Chinese name)	PEG600 雙油酸酯
外觀(appearance) 25℃	微黃色液體 yellowish liquid
水份 WATER content%	0.5 max
色度 COLOR(apha)	300 max
酸價 Acid value (mg KOH/g)	7.0 max
PH 2% aq	6.0~7.0
曇點 Cloud point (25% BC aq, ℃)	27~31
皂化價 Saponification Value (mg KOH/g)	95~101
包裝 PACKING	200 kg/iron drum

## 用途:

溶於水,具有良好的洗滌、乳化、潤滑性能。化妝品中作 O/W 乳化劑,紡織業中作勻染劑、分散劑、柔軟劑,金屬加工中作潤滑劑。農藥中作殺蟲劑的乳化劑,亦可用於水溶性塗料、印刷電路板的酸洗

#### Application:

It is soluble in water and has good washing, emulsifying and lubricating properties. As an O/W emulsifier in cosmetics, it is used as a leveling agent, dispersant and softener in the textile industry, and as a lubricant in metal processing. As an emulsifier for pesticides in pesticides, it can also be used for pickling of water-soluble paints and printed circuit boards. O/W emulsifier in cosmetics, it is used as a leveling agent, dispersant and softener in the textile industry, and as a lubricant in metal processing. As an emulsifier for pesticides in pesticides, it can also be used for pickling of water-soluble paints and printed circuit boards.